


Extruded Brackets -for 1-slot-

20,25,40

-Slot Type: HFS5 Series (Aluminum Frames 20, 25, 40 Square)-








Part Number	Mass	Applica	Unit Price	Volume Discount Rate				
Part Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~
HBKTST5						40	38	
HBKTS5	15	CBM5-10	2	HNTT5-5	2	833	38	37
HBKTSB5* (Black Anodize)	15	ODIVID-10					60	57


^{*} For repairing black anodizing, refer to P.748






Part Number	Mass	Applica	Unit Price	Volume Discount Rate					
	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~	
HBLTS5		CBM5-10		HNTT5-5					
HBLTS5-4 (For M4 Bolt)		CBM4-10		HNTT5-4			93	89	
HBLTSB5* (Black Anodize)	20	15		2		2	833	157	150
CHBLTS5 (Clear Coating)		CBM5-10	2	HNTT5-5	-	000	150	142	
HBLTV5							135	130	
HBLTVB5* (Black Anodize)		20			220	210			

* For repairing black anodizing, refer to P.748




Features: Numbers of screws are the same as HBKTS8. Extrusions can be connected more securely.




Part Number	Mass	Applica	crew / T Nut	Allowable Load	Unit Price	Volume Discount Rate			
Part Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~	
HBKUS5							52	49	
HBKUSB5* (Black Anndize)	31	CBM5-14	2	HNTT5-5	2	2	833	80	76

Features: Numbers of screws are the same as HBLTS8-45. Extrusions can be connected more securely.



• CAD Data Folder Name: 40_Aluminum_Frames

Features: Hole positions are eccentric. Can be combined with plates of 5mm and 3mm thickness when using taps for mounting covers.



Part	Mass	Applical	ole S	crew / T Nut		Allowable Load	Unit Price	Volume Discount Rate	
Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~	
HBLTH5							32	31	
HBLTHB5* (Black Anodize)	15	CBM5-10	2	HNTT5-5	2	833	54	51	

THBLTH5 and HBLTHB5 are eccentric. Can be combined with both cover plates of 5mm and 3mm thickness.



* For repairing black anodizing, refer to P.748


Features: Extruded Brackets with twice as many screws. Extrusions can be connected more securely.



Туре	Material	Surface Treatment 7	14	9.5
HBLTSW5 HBLTVW5	A6N01SS-T5	Anodize	7	9.5
		HBLTSW5	50 57	25 Square 5
		$ _{\Phi}$		HBLTVW5
				30
		4-05.5	121	4-05.5
			04.2	12 04.2
		30	7	30
		5 20 57		5 20 57
		1 3/		

Part Number	Mass	Applica	ble S	crew / T Nut	Allowable Load	Unit Price		
Part Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~
HBLTSW5	26	CBM5-10	4	HNTT5-5	4	1176	76	72
HBLTVW5	36		4	HIVI 13-3	4	1170	74	70

Features: Extruded Brackets Unequal Sides. Effective when strength is required in the narrow clearances between extrusions.



Part	Mass	Applical	ole S	crew / T Nut		Allowable	Unit Price	Volume Discount Rate	
Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	. 100~	
HBLTF5	21	CBM5-10	3	HNTT5-5	3	1004	79	74	



Part Number







Alterations	Code	Spec.	Applicable Brackets	Price Adder			
			HBLTS5	14			
			HBLTS5-4	14			
			CHBLTS5	23			
			HBLTV5	19			
Mounting		HBLTVB5		19			
	_	Adds taps on a bracket for cover	Adds taps on a bracket for cover HBLUS5				
Holes for		c mounting.		HBKTS5			
				(M5 on Both Sides)	(M5 on Both Sides)		HBKUS5
Cover			HBLUS5	14			
		(mounting coron fro fr mount)	HBLTH5				
		HBLTHB5 HBLTSW5					
			HBLTVW5	19			
			HBLTF5	14			

	Alterations	Code	•								
			Spec.	Applicable Brackets		- 1	Pric	e Ad	ddeı	r	
			Supplies a set of applicable screws		SET	SST	SEU	SSU	SEP	SSP	SEC
		SET	and nuts for fixing the bracket to a extrusion.	HBLTS5	38	28	49	75	49	57	57
		SST	(Adds to the bracket price)	HBLTS5-4						-	
		(Stainless Steel)	(Ex.) When HBLTS5 is specified,	HBLTSB5	40	-	51	-	51		_
;)		(Pre-assy, Insertion Spring Nuts)		CHBLTS5	38	28	49	75	49	E7	57
		SSU	Code Screws Nuts SET CBM5-10 HNTT5-5	HBLTV5	30	20	43	13	43	31	JI
		/Pre-Assy. Insertion	SST SCB5-10 HNTTBS5-5	HBLTVB5	40	-	51	-	51		
	Applicable	Spring Nuts Stainless Steel	SEU CBM5-10 HNTU5-5	HBKTST5	38 28	28	49	75	49	E7	57
	Screws and	SEP	SSU SCB5-10 SHNTU5-5	HBKTS5	38	20	49	/3	49	37	31
	Nuts come as		SEP CBM5-10 HNTP5-5	HBKTSB5	40	-	51	-	51		
	a set.	Spring Nuts	SSP SCB5-10 SHNTP5-5	HBLUS5							
		/Pre-Assy, Insertion \	SEC HCBST5-12 HNTT5-5	HBKUS5	39	28	50	75	50	5/	59
		Spring Nuts	• When specifying other than HBLTS5, check for the applicable screws and	HBKUSB5	41	-	52	-	52		
		SEC Stainless Steel /	nuts.	HBLTH5	38	28	49	75	49	57	57
		/Captured Washer\	nuts.	HBLTHB5	40	-	51	-	51		
		Screws		HBLTSW5	7.		07	450	07	,,	
		\ Nuts /		HBLTVW5	75	55	9/	150	9/	113	-
				HBLTF5	56	41	74	112	74	85	85
	Screws for	black anodize	ed parts are HCBMTB (Trivalent Ch	romate Black)	. P.6	41					

When -SET, -SEU or -SEP is specified, it is not RoHS compliant.