

SILICONE HOSE FOR HIGH TEMPERATURE WATER / RESIN HOSE FOR TEMPERATURE CONTROL

■ Silicone Hose for High Temperature Water (Heat resistance 170°C)



Internal dia.	External dia.	Allowable pressure (MPa)	Usable temperature	Allowable bending radius	Weight (g/m) *Reference value	Part Number		Total length 1m increments	Unit Price (1~9 pcs) 1~20M (Per 1m)
						Type	No.		
7.9	14	0.58	170°C or less	70	160	M-NHC	8	1~20	Quotation
9.5	16.2	0.55			240				
12.7	19.3	0.55			275				
15.9	23.5	0.48			300				
19	27.2	0.48			380				
25.4	35	0.34			515				
					16				
					19				
					25				



Order

Part Number — Total length

M-NHC 13 — 15



Days to Ship


Quotation



Price

Quotation

■ Resin Hose for Temperature Control



■ Features

- General purpose hose with excellent transparency.
- Use water at temperatures of 60°C or lower.

Nominal dia.	Internal dia. × External dia.	Usable temperature	Allowable pressure (20°C) MPa or less [Kgf/cm ² or less]	Allowable bending radius	Weight (g/m) *Reference value	Part Number		Total length 1m increments	Standard size (m)	Unit Price (1~4 pcs)						
						Type	No.			L dimension designation (Per 1m)	Standard size					
4	4.0×9.0	60°C or less	1.00 [10.2]	35	65	M-HNT	4	1~99	100	Quotation						
6	6.0×11.0			40	85						6					
8	8.0×13.5			55	115						8					
9	9.0×15.0			60	145						9					
10	10.0×16.0			70	155						10					
12	12.0×18.0			75	180						12					
15	15.0×22.0		0.80 [8.2]	95	245		15	1~49	50							
19	19.0×26.0			135	300							19				
25	25.0×33.0			0.60 [6.1]	165							440	25	1~39	40	
32	32.0×41.0				210							640				
38	38.0×48.0	255	815		38											
50	50.0×62.0	0.50 [5.1]	380	1300	50											



Order

Part Number — Total length

M-HNT 12 — 53

M-HNT 32 — 50



Days to Ship

Quotation



Price

Quotation